



Fire Apparatus Quotation for: NEW PORT RICHEY



Quotation Number: 95328 Rev: 101

Unit Description: AERM-TYPH-075L

Quote Description: Aerial Rear Mount, Typhoon, HP75 Ladder Salesperson: CBEVILLE

Salescode	Extended Description	Qty
FRAME ASSEMBLY		
1250-0080	Frame assembly with 10.25 x 3.5 x .375 powder coated galvanized rails.	1
1250-0083	Frame liner 9.375 x 3.125 x .375, galvanized and powder coated.	1
1250-0092	GEOMET coated frame assembly fasteners.	1
AXLE OPTIONS		
1025-0013	Meritor FL-943 front axle 21,500 lbs.	1
1025-0028	Koni shock absorbers for front axle - adjustable.	1
1025-0030	Stemco oil seal front axle. Chicago Rawhide seal with Stemco sight glass will be supplied when front disc brakes are selected.	1
1025-0097	Meritor RS-30-185 single rear axle 33,000 lb. capacity. Requires 16.5" x 8.625" cast shoe brakes and 33K suspension.	1
SUSPENSIONS		
1070-0017	Reyco 33K rear spring suspension w/auxiliary springs.	1
TIRE OPTIONS		
1060-0043	Two Michelin 425 tires model XZY3 for front axle.	1
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1
1060-0174	Four Michelin 315 tires model X Multiway 3D XZE for rear axle	1
BRAKE SYSTEMS		
1100-0001	Meritor EX225H 17" disc brakes for front axle.	1
1100-0005	Brake system air 4X2/4X4.	1
1100-0006	Parking brake release mounted on the driver's side lower dash.	1
1100-0036	16.5" x 8.625" P-Cast S-cam brakes for 27,000 - 35,000 Meritor axle.	1

Salescode	Extended Description	Qty
TESTING COMPLIANCE STANDARD		
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1
3090-0002	OAH. Unit has no overall height restrictions.	1
3090-0004	OAL. Unit has no overall length restrictions.	1
3090-0006	The hose bed is to have the capacity for the following hose. Hose load shall be listed from driver to officer.	1
3340-1137-12C	Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1
BUMPER TRAYS		
1150-0273	Nylon black cargo net with black powder coated quick release buckles on sides for bumper crosslay.	1
1150-0471	Recessed bumper double crosslay to hold 200' of 1.75" DJ hose in rear crosslay and 100' of 1.75" DJ hose in front crosslay. The crosslay floor/bottom shall be slotted to allow drainage (no slats). Includes full width hinged bi-fold raised lid and stainless steel scuff guards at each side and bottom of crosslay opening (exclude bottom if drop down covers are used). Requires 28" extension, side covers, 12" heavy duty bumper and engineering approval.	1
BUMPERS		
1160-0016	28" Front Bumper Gravel Shield Extension.	1
1160-0084	Heavy duty 12" front bumper with full wrap around. To be painted job color.	1
1160-0138	3/16" Front Bumper Gravel Shield. Extend shield to flush with heavy duty bumper edge.	1
1160-0142	Front frame extensions to be drop style IPOS. Includes integral tow eyes below bumper.	1
WHEEL OPTIONS		
1050-0007	Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals.	1
1050-0008	Rear axle (single) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers.	1
1050-0017	Each inside wheel of the single rear axle shall have valve stem extensions.	1
1050-0044	Accuride aluminum wheels for front axle (2).	1
1050-0045	Accuride aluminum wheels for rear axle (4).	1

Salescode	Extended Description	Qty
AIR SYSTEM OPTIONS		
1110-0000-001	Inlet for air system. Location: driver door jamb.	1
1110-0002	Air dryer Bendix AD-9.	1
1110-0006	Air lines nylon.	1
1110-0013	Air horns shut-off valve. Located in cab accessible by driver.	1
1110-0026	Air horns recessed in bumper (PR).	1
ENGINES & TRANSMISSIONS		
1200-0017	Push-button transmission shift selector.	1
1200-0020	Transynd, Shell Spirax S6ATF A295, or equivalent synthetic transmission fluid for EVS3000.	1
1200-0096	Electronic speed limiting set at 60 MPH.	1
1200-0341	Eng/Trans Cummins L9 450HP/EVS3000 2017 EPA compliant engine.	1
SECONDARY BRAKING		
1125-0002	Jacobs engine compression brake.	1
1125-0023	Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder.	1
EXHAUST OPTIONS		
1225-0008	Wrap exhaust with heat tape from the turbo down to the flex pipe. Inspect after install for tears in material. Wrap outside with wire mesh to ensure material remains affixed.	1
COOLING PACKAGE		
1800-0013	Cooling system for use with Cyclone II X, Typhoon X, and Quest chassis. For use with 2010 - 2018 EPA engines. Includes coolant recovery system.	1
1800-0029	Engine cooler. E-ONE chassis only. Requires control option for pump panel.	1
FUEL SYSTEMS		
1350-0005	Fuel system 65 gallons.	1
1350-0012-670	Fuel shut-off valve. Location: one (1) inlet side of OEM fuel filter.	1
1350-0022	Fuel line hose rubber.	1
ALTERNATOR		
1700-0027	Alternator Leece Neville 420 amp. 420 amp SAE/369 amp NFPA.	1
BATTERIES		

Salescode	Extended Description	Qty
BATTERIES		
1400-0002	Battery four group 31 1000 CCA.	1
CHASSIS OPTIONS		
1680-0005	Thermatic fan clutch.	1
1680-0006	Drivelines 1710.	1
1680-0012	Tow eyes rear frame painted black.	1
1680-0051	Aerial hydraulic activation system.	1
1680-0250-M58	Diesel Exhaust Fluid (DEF) 5 gallon tank. Location: left side below rear of cab.	1
CAB MODEL		
1520-0012	Typhoon X long cab with 67.5" CA	1
CAB ROOF TYPE		
1615-0021	Split raised rear cab roof. 12" high for use with rear mount aerial.	1
CAB BADGE PACKAGE		
1610-0000	Cab and body to have applicable E-ONE logos.	1
GRILLE		
1620-0006	CIIX stainless steel grille for Typhoon X.	1
CAB DOOR OPTIONS		
1550-0003	Rear crew cab doors in the medium position.	1
1550-0006	Driver and officer cab door windows. Include rear fixed window.	1
1550-0013	Driver and Officer door windows. Includes electric roll-down actuation. Each door to have individual control at door position and the driver door is to have master control for all power window locations.	1
1550-0015	Stainless steel protective trim on rear edge of cab door openings. E-ONE custom chassis only.	1
1550-0017	Cab door panels stainless steel.	1
1550-0024	All cab doors shall have exterior paddle latches.	1
1550-0038-659	(4) LED cab step area lighting. Locate each light on each cab door in the inboard position. Lights to be switched with door ajar.	1
1550-0069-000-J7	Reflective Red/Fluorescent Yellow Green 3M Diamond Grade striping positioned in the "A" formation located on the cab door panels.	1
1550-0081	Cab door locks - electric. Includes driver side exterior touchpad, (2) remote key fobs, barrel style key lock on exterior of each door and manual interior lock on	1

Salescode	Extended Description	Qty
CAB DOOR OPTIONS		
	each door.	
1550-0084	All cab exterior access doors to have 1250 keyed locks.	1
1550-0102	Rear crew cab door windows with rear fixed panel. Includes electric roll-down actuation. Each door to have individual controls. For use with paddle style door latching.	1
1550-0250	Tri-Mark cab door interior paddle latch assembly. Includes front and rear cab doors. Rotate rear interior cab door paddle latches 90 degrees. Operator to pull up to open cab doors. Not available with ABS door panels.	1
CAB STEP OPTIONS		
1640-0045-158	Step below cab door. Open back style with angled corners. Located driver's front door. Steps under front cab doors shall not interfere with approach angle.	1
1640-0045-159	Step below cab door. Open back style with angled corners. Located officer's front door. Steps under front cab doors shall not interfere with approach angle.	1
1640-0045-160	Step below cab door. Open back style with angled corners. Located driver side rear door. Steps under front cab doors shall not interfere with approach angle.	1
1640-0045-161	Step below cab door. Open back style with angled corners. Located officer side rear door. Steps under front cab doors shall not interfere with approach angle.	1
MIRRORS		
1670-0001-274	Ramco 6001FFR mirrors. Remote controlled with top CAS750 convex. Location: mounted on front corners of cab.	1
1670-0031	2" extension for Ramco mirrors.	1
MISC EXTERIOR CAB OPTIONS		
1550-0035	No window on the driver side of the cab	1
1550-0036	No window on the officer side of the cab.	1
1675-0022	Pair of 18" handrails located just behind driver and officer front door one each side.	1
1675-0024	Pair of 36" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side.	1
1675-0030	Mud flaps, front, black with E-ONE logo.	1
1675-0046	Rear cab wall to be smooth 3/16" aluminum plate. Cab wall to be finish painted to match the cab paint scheme.	1
1675-0201	Large radius cab wheel well. Includes bolt-on adjustable wheel well trim.	1
1675-0212	Mounting plate for battery charger receptacle, indicator, air inlet, etc (if applicable). Plate to be removable polished stainless steel.	1

Salescode	Extended Description	Qty
HVAC		
1515-0017	Air conditioning for the Typhoon X, CII X and Quest with Cummins ISC/ISL engine and radiator mounted condenser.	1
1515-0053	Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and CII with severe duty dash)	1
SEATS		
1510-0003	Seats, Inc. brand 911 cab seats.	1
1510-0008	Seat color gray.	1
1510-0038	Driver seat 911 air ride.	1
1510-0041	Officer seat 911 air ride SCBA.	1
1510-0062	Two man bench centered on rear wall with 911 SCBA backs. Includes angled corners.	1
1510-0203-147	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: officer's seat.	1
1510-0203-151	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: inboard driver's side rear wall.	1
1510-0203-152	Bracket SCBA IMMI SmartDock Gen2 restraint system. Location: inboard officer's side rear wall.	1
1510-0234	Seat cover material Turnout Tuff.	1
1510-0279-146	ReadyReach seat belt extender. Location: driver's seat.	1
1510-0279-147	ReadyReach seat belt extender. Location: officer's seat.	1
1510-0279-151	ReadyReach seat belt extender. Location: inboard driver's side rear wall.	1
1510-0279-152	ReadyReach seat belt extender. Location: inboard officer's side rear wall.	1
1685-0031	Seating capacity tag of four occupants.	1
MEDICAL CABINETS		
1535-0012	Medical cabinet interior mounted on the wheel well driver side of cab 45H x 21W x 24D with a locking roll-up door.	1
1535-0013	Medical cabinet mounted on the wheel well officer side of cab 45H x 21W x 24D with a locking roll-up door. Extra low waterway roof height is 42" instead of the required 45".	1
1535-0030	All roll-up medical cabinet doors selected on the cab to be ROM brand.	2
1535-0032	All medical cabinet RUD in the cab to be locking with 1250 key	1
1535-0202	Cab medical/storage cabinet(s) finish to be Zolatone gray. Includes interior/exterior of cabinet and shelves/trays if equipped.	1
MISC INTERIOR CAB OPTIONS		

Salescode	Extended Description	Qty
MISC INTERIOR CAB OPTIONS		
1680-0053	Storage below rear bench seat. (1) hinged door on each side of the bench seat.	1
1685-0000	Cab interior gray. Does not include engine cover or seat color.	1
1685-0006	Padded sun visors, driver and officer's side overhead.	1
1685-0059	Locking seat riser door. Driver and officer seat riser doors are to include a locking push-button latch. Key type to be 1250.	1
1685-0084	3/16" Aluminum plate on top engine access door. To have swirl finish and be spaced up approx 1/2".	1
1685-0094	Storage below rear bench seat. (1) horizontal hinged door on the front of the rear bench seat.	1
1685-0116	Interior grab handle rubber covered (2). Locate one each side at interior of front cab door opening (at rear of opening).	1
1685-0187	Severe duty engine cover, molded polyurethane.	1
1685-0369	Severe duty dash package with low profile officer side dash. Includes smooth plate alum center and officer side dash and lower kick panels; all painted to match cab interior.	1
1685-0422	Severe duty overhead console. Includes front full width overhead, air conditioning plenum and rear facing blower. Overhead to match cab interior.	1
1685-0423	Driver side severe duty dash. Includes driver side aluminum upper dash to match cab interior with ABS gauge cluster.	1
1685-0431	Storage below rear facing seat riser (PR).	1
1685-0532	Stepped profile rear engine cover.	1
1685-0656	Storage box locking, mounted on the top of wheel well medical cabinet. Lock box measures 5x12x10 with a lift top lid and a 1250 keyed, locking latch. Finish will match cab interior.	1
CAB ELECTRICAL OPTIONS		
1750-0024-179-04	Auto-Eject receptacle inlet 20 amp located outside driver's door next to handrail with a Yellow cover.	1
1750-0027	Control push-button switch officer dash for Q2B siren.	1
1750-0032	Switch horn button three position DOT/air horn/electronic siren.	1
1750-0046-194	Cab Headlights. Position: upper.	1
1750-0061	Control push-button switch officer dash for air horns.	1
1750-0062	Control push-button switch officer dash for siren.	1
1750-0072-545	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1
1750-0072-546	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: In cab officer	1

Salescode	Extended Description	Qty
CAB ELECTRICAL OPTIONS		
1750-0072-593	side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush). 12 VDC (or 24VDC) electrical outlet wired battery hot. Location: officer side dash.	1
1750-0072-747	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: driver side rear cab wall in or below seat support structure as space allows.	2
1750-0072-748	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: officer side rear cab wall in or below seat support structure as space allows.	2
1750-0072-763	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: rear wall of driver side medical compartment up high.	1
1750-0072-764	12 VDC (or 24VDC) electrical outlet wired battery hot. Location: rear wall of officer side medical compartment up high.	1
1750-0073-587	Antenna base Tescos P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: officer side forward with coaxial cable terminating at the center of the dash board.	1
1750-0073-588	Antenna base Tescos P/N 90942 (NMO Motorola Style - also called MATM style) on cab roof. Location: officer side rearward with coaxial cable terminating at the center of the dash board.	1
1750-0075	English dominant main cab gauge cluster.	1
1750-0149	Control push-button switch officer dash for Q2B siren brake.	1
1750-0198-A31	Battery charger to be located behind driver's seat.	1
1750-0265	Speedometer for officer side multiplex display.	1
1750-0343	Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output.	1
1750-0429-545	Dual USB charging ports in the cab wired battery hot. Location: In cab driver side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1
1750-0429-546	Dual USB charging ports in the cab wired battery hot. Location: In cab officer side on 3 x 3 post rear facing just above engine cover (or seat riser if in a Hush).	1
1750-0429-593	Dual USB charging ports in the cab wired battery hot. Location: officer side dash.	1
1750-0429-763	Dual USB charging ports in the cab wired battery hot. Location: rear wall of driver side medical compartment up high.	1
1750-0429-764	Dual USB charging ports in the cab wired battery hot. Location: rear wall of officer side medical compartment up high.	1
1750-0447	Dome Lts Red/White Whelen model 60REGCS LED. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wired through door and light assembly switch. Red light through light assembly switch.	1
1750-0449	Momentary DPF regeneration override switch.	1
1750-0554	FireTech LED cab headlights.	1

Salescode	Extended Description	Qty
CAB ELECTRICAL OPTIONS		
1750-0582	Light EON LED (EA) mounted in bench seat riser. The light(s) shall be wired through the compartment door switch(s).	1
1750-0651-173	Turn signal Whelen C-Series model C6T LED amber arrow pair located lower headlight bezel.	1
1750-0666	Aerial PTO hourmeter in cab.	1
BODY MODEL		
3080-0220	Body eMAX aerial HP75/78 with combined standard height front side compts and center hose bed. Configured for midship pump and 400-500 tank. Single axle 100" wide body.	1
BODY COMPT REAR		
3110-0027	Rear body panels to be un-painted extrusions with un-painted smooth plate body panels or just unpainted smooth plate to facilitate rear body striping.	1
AERIAL BODY OPTIONS		
3310-0032	Recessed tubes for (6) pike poles. Not available on HP75 SideStacker.	1
3310-0069	Rear ladder tunnel doors. Vertically hinged smooth plate to match rear body finish.	1
3310-0292	Jack leg opening covers brushed finish S/S (2) sets. Includes outrigger covers and fixed filler panels. For HP75/78 and Tiller.	1
3310-0314	Auxiliary jack pad 24X24 (2) with 20 degree formed handle. Includes mounting brackets.	1
DOORS		
3300-0017-004	Door roll up short (up to 45") with satin finish ROM. Location(s): L2.	1
3300-0017-005	Door roll up short (up to 45") with satin finish ROM. Location(s): L3.	1
3300-0017-016	Door roll up short (up to 45") with satin finish ROM. Location(s): R2.	1
3300-0017-017	Door roll up short (up to 45") with satin finish ROM. Location(s): R3.	1
3300-0019-003	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L1.	1
3300-0019-006	Door roll up tall (greater than 45") with satin finish ROM. Location(s): L4.	1
3300-0019-015	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R1.	1
3300-0019-018	Door roll up tall (greater than 45") with satin finish ROM. Location(s): R4.	1
3300-0019-864	Door roll up tall (greater than 45") with satin finish ROM. Location(s): driver side pump panel.	1
3300-0019-033	Door roll up tall (greater than 45") with satin finish ROM. Location(s): right side compartment opposite pump panel.	1

Salescode	Extended Description	Qty
SHELVES		
3370-0246	Adjustable shelf for non-transverse compartments. Location:	16
		2-R1 1-L1 1-L2 1-L3 2-L4 3-R1 2-R2 2-R3 1-R4 2-RP
3370-0247	Tracks for adjustable shelf and/or adjustable tray in a compartment. Location:	16
		R1 R2 R3 R4 RP L1 L2 L3 L4 ALL SHELVES TO BE ADJUSTABLE
COMPARTMENT DIVIDERS		
3390-0557	Partition, bolt-in vertical partition wall. Location:	1
		L1
TRAYS / TOOLBOARDS		
3380-0498	Tray, floor mounted roll-out with gas spring. 500 lbs. capacity. Location:	2
		L1 R1
3380-0508	Adjustable heavy duty tool board with 500 lbs. capacity. Includes return style reinforcing bends on vertical front and rear edges of tool board, upper and lower adjustable track and gas shock actuated. Tool board sized to compartment height and depth as applicable. Location:	1
		L1
3380-0567	Adjustable mounted aluminum SlideMaster roll-out/tilt down model MT with aluminum tray. Location(s):	1
		L1
COVERS		
3305-0023	Nylon black cargo net at rear of diamond plate or vinyl hose bed cover or similar.	1
3305-0027	Nylon black cargo net on sides of speedlay. One pair per opening.	1
3305-0034-000-13	Vinyl Black hose bed cover without rear flap(s). Requires rear cover option.	1
PUMP MODULE		
3130-0421	eMAX Pump module HP75/78. Includes enclosed pump panel, compt on officer side (opposite pump panel), lower and upper storage areas, center front pump access doors, removable center floor in upper area, storage pan and boom support diamond plate filler panels. Lower storage area to hold (1) tray for 200' of 1.75" DJ preconnected hose and (1) tray for 200' of 2.5" DJ preconnected hose. Upper storage area to hold (1) tray for 200' of 1.75" DJ preconnected hose offset to rear and storage area for (2) backboards vertically stored offset forward w/sleeve each side of center pump access.	1
PUMP PANELS		
3134-0079	The side pump intake / discharge panels to be stainless steel. eMAX only.	1
3134-0080	Pump operator control panel in driver side forward body compartment to be stainless steel. eMAX only.	1
MISC PUMP PANEL OPTIONS		
4460-0000-282	Air outlet w/snubber valve. Location: driver's side pump panel.	1

Salescode	Extended Description	Qty
MISC PUMP PANEL OPTIONS		
4460-0003	Pump panel tags color coded per NFPA compliance.	1
4460-0058	Push-pull handles on the pump operator's panel to be oriented vertical. eMAX only.	1
PUMP MODULE OPTIONS		
3136-0138	Pump module storage pan.	1
3136-0205	Removable Aluminum Hose Tray(s) with slotted floor to prevent the accumulation of water and allow for ventilation of wet hose. Includes vertical slotted hand hold cutouts on each end to facilitate easy removal of the hose tray. No lip, No grab rod.	3
WATER TANK		
4010-0198	500 gallon "T" water tank. UPF Poly III blue fill tower.	1
TANK PLUMBING		
4450-0010	2" tank fill Akron manual valve.	1
4450-0023	3" Tank to Pump Akron Air Actuated Valve	1
FOAM TANK		
4100-0035-590-16	20 gallon integral foam tank for Class A foam. UPF Poly III Green fill tower. Foam tank capacity will reduce the water tank capacity.	1
LADDER STORAGE / RACKS		
3365-0015-809	Dual ladder tunnel for HP75 / HP78. Ladder rack to hold: PEL3-35, PEL-24, (2)PRL-16 and FL-10 with rubber block feet. Requires roof ladder option on base section of aerial to meet 115' NFPA requirement	1
3365-0016	Box type enclosure for forward end of ladder tunnel. Required on center HB HP75 / HP78 with ladder tunnel doors.	1
HANDRAILS / STEPS		
3330-0002-050	Slide-out platform, rollerless. Includes chrome grab handle centered on the front face of the platform (includes hand rail as applicable). Located below driver side pump panel.	1
3330-0158	Step below side intake / discharge panel (PR). Gator grip diamond plate. Each location requires a minimum of (1) handrail / handhold per NFPA. eMAX only.	1
3330-0242	Flop down 36" wide step (EA) fabricated from .125" diamond plate with gator grip to be located at rear of body for access to turntable. Includes mechanical lock to store in the up and stored position.	1
MISC BODY OPTIONS		

Salescode	Extended Description	Qty
MISC BODY OPTIONS		
3340-0077	Body compartment Interiors to have Zolatone gray finish. To include pan of hinged doors and tool compartments (as applicable). Does not include floors if they are diamond plate. Does not include roop top compartments if equipped.	1
3340-0093	Mud flaps, rear, black with E-ONE logo.	1
3340-0282-032	Cab tilt switch and manual jack to be located: right side compartment opposite pump panel low on forward wall.	1
3340-0486	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and bolt-on polished alum fenderettes.	1
3340-1649	Brushed stainless steel trim on bottom edge of all body compartment openings with painted edge. Small and medium aluminum bodies.	1
SCBA BOTTLE STORAGE		
3320-0020	SCBA Bottle Storage. (4) Fire Shopp SCBA single bottle storage with hinged doors with push button latches. (2) officer side and (2) driver side in wheel well area.	1
3320-0100	Strap, loop style to retain SCBA bottle(s). Locate one per bottle in each exterior body storage compartment.	1
PUMPS		
4005-0031	Rating 1500 GPM.	1
4005-0204	E-ONE 1250-1500 GPM pump, single stage. Requires primer option.	1
PUMP CERTIFICATION		
4475-0000	Pump certification 750-2250 GPM	1
PUMP OPTIONS		
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1
4015-0073	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location below running board on driver side (or area directly to rear of panel if no room below panel).	1
4015-0133	Anode for Darley pump - (1) intake side.	1
4015-0210	Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label.	1
4015-0234	Control for engine cooler. Includes Innovative Controls 1/4 turn valve with "T" handle and label. Requires engine cooler option.	1
4015-0242	Trident primer W/3 barrel push button control. For use with 1250 GPM and larger pumps. Requires 15.6 CFM or larger engine air compressor.	1
INTAKES		

Salescode	Extended Description	Qty
INTAKES		
4440-0005	2.5" Left Intake Akron Manual Valve.	1
4440-0006	2.5" Right intake Akron manual valve.	1
INTAKE OPTIONS		
4445-0048	Intake pressure relief valve, Task Force Tips.	1
DISCHARGES AND PRECONNECTS		
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1
4415-0016-584	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2.	1
4415-0552	1.5" Front Bumper Crosslay Discharge Akron Manual Valve.	2
4415-0858	Triple speedlay with (1) 1.5" and (1) 2.5" in lower storage area and (1) 1.5" in upper storage area. All with Akron manual valves.	1
4415-0957	Speedlay plumbing in lower opening to have 1.5" forward and 2.5" rearward.	1
4415-1219-583	4" Panel discharge w/ Akron electric valve and cap. Requires valve controller option. Location: right side discharge 1.	1
4415-1274	4" waterway discharge w/ Akron electric valve. Requires valve controller option.	1
DISCHARGE OPTIONS		
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	10
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1
4417-0313-359	AKron 9333 Navigator Pro 2 electric valve controller with full color LCD display. Locate on pump operator panel to control waterway discharge.	1
4417-0313-583	AKron 9333 Navigator Pro 2 electric valve controller with full color LCD display. Locate on pump operator panel to control right side discharge 1.	1
PRESSURE GOVERNORS		
4465-0028	Class 1 Sentry pressure governor/ Twister throttle. Includes master intake and discharge gauges, water, oil, tran, volt and tachometer.	1
GAUGES		
4435-0034	Fuel level gauge on pump operator's panel.	1

Salescode	Extended Description	Qty
GAUGES		
4435-0084	Innovative Controls 10 LED series foam tank level gauge. On pump panel.	1
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	10
4435-0347-527	IC 10 LED SL series/Whelen PSTank2 water tank level gauge package. Location of Whelen PSTank2 Strip Lights: each side of cab rear of front doors.	1
FOAM SYSTEMS		
4430-0079	The foam system performance shall be tested and certified in compliance with the applicable NFPA 1901 requirements.	1
4430-0159	Class 1 2.1A foam system with SmartFoam controller.	1
FOAM SYSTEM OPTIONS		
4432-0053-0DG	Foam system plumbed to front bumper crosslay 2.	1
4432-0053-562	Foam system plumbed to 1.5 first speedlay.	1
4432-0053-563	Foam system plumbed to 1.5 second speedlay.	1
4432-0053-Z16	Foam system plumbed to front bumper crosslay 1.	1
ELECTRICAL SYSTEMS		
5010-0039	V-MUX Electrical system for aeriels.	1
5010-0049	Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only.	1
5010-0055-168	Vista IV display for V-MUX electrical system. Location: officer's side engine cover.	1
5010-0055-649	Vista IV display for V-MUX electrical system. Location: driver's side engine cover.	1
5010-0094	Nanoprotech corrosion inhibiting spray coating to be applied on all exposed electrical connections.	1
5010-0100	AXIS Smart Truck Technology. Includes roof mounted antenna and 5 year data plan. For use only with E-ONE chassis in the USA.	1
LIGHT BARS		
5300-0506-000-4V	Front light bar LED color: Red/White with clear lenses (If applicable, includes side facing when colors are the same.)	1
5300-0514	Whelen MK9S short slide bolt bracket mount for mini front light bars (4).	1
5300-0524-034	Whelen F4 Mini-Freedom LED light bars (PR) 21.5" with 5 LEDs in each bar. Location: front cab corners.	1
WARNING LIGHT PACKAGES		
5550-0483-065-4T	Whelen C-Series model C6L Super LED lower level warning light package. Includes (10) light heads with bezels. Color: Red with clear lenses. Locate side	1

Salescode	Extended Description	Qty
WARNING LIGHT PACKAGES		
	facing lights: at forward most position, on side of cab centered over wheel well, and on rear fixed outrigger cover.	
WARNING LIGHTS		
5600-0074-189	Opticom Emitter 3M #792H. Emitter and control only. Wire through parking brake. Location: front of cab above grille.	1
5600-0105-170	Hazard (door ajar) light 2" LED. Location: center overhead.	1
5600-0177	Whelen model UFM8 LED flasher (3). Flashers will control warning lights ipointernal flashers. Locate (1) in cab and (2) in body.	1
5600-0423-457	Warning light Whelen Rota-Beam series model 6RBRC Super LED (PR) red with clear lenses. Location: (1) each side of body rear facing up high.	1
5600-0669-3C8-4T	Warning light Whelen C-Series model C6L Super LED (PR). Color: Red with clear lenses. Location: (1) each side of cab, rearward of rearward doors, same height as warning light(s) over front wheel well.	1
5600-0669-439-4U	Warning light Whelen C-Series model C6L Super LED (PR). Color: Red with red lenses. Location: (1) each side above quad bezel (outboard).	1
5600-0669-460-4U	Warning light Whelen C-Series model C6L Super LED (PR). Color: Red with red lenses. Location: (1) each side of cab centered over wheel well.	1
5600-0669-467-4U	Warning light Whelen C-Series model C6L Super LED (PR). Color: Red with red lenses. Location: (1) each side above tail lights.	1
5600-0671-468-4T	Warning light Whelen ION-T Series model TLI Super LED (PR). Color: Red with clear lenses. Location: (1) each side facing at rear of body in rubrail if equipped. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	1
5600-0671-469-4T	Warning light Whelen ION-T Series model TLI Super LED (PR). Color: Red with clear lenses. Location: (1) each side centered below forward compartments in rubrail if equipped. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	1
5600-0671-471-4T	Warning light Whelen ION-T Series model TLI Super LED (PR). Color: Red with clear lenses. Location: (1) each side just behind rear wheels in rubrail if equipped. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	1
5600-0671-M57-4T	Warning light Whelen ION-T Series model TLI Super LED (PR). Color: Red with clear lenses. Location: (1) each side rear wheel well centered. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only -	1

Salescode	Extended Description	Qty
WARNING LIGHTS		
	NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	
DIRECTIONAL LIGHT BARS		
5310-0020-846	Directional light bar control is to be located center overhead console offset to driver side.	1
5310-0025	Directional light circuit wiring through upper level warning.	1
5310-0028	Whelen Traffic Advisor Model TAM83 LED - 31" long, with clear lenses.	1
SIRENS		
5500-0009	Federal PA300 electronic siren recessed mounted.	1
5500-0010-210	Federal Q2B siren - flush mounted in bumper. Location: center front bumper. Requires activation switch.	1
5500-0024-847	The primary electronic siren control is to be located center overhead console offset to officer side.	1
SPEAKERS		
5510-0029-209	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper.	1
5510-0029-211	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: officer side front bumper.	1
DOT LIGHTING		
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1
5150-0026	Marker light Truck-Lite LED body/cab package. E-ONE custom cab with aerial ladder, Mid-Mount platform or Bronto bodies only.	1
5150-0032	Bracket license plate at rear of body.	1
5150-0215	Whelen C6 series LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical chrome ABS 4 housing and weatherproof connectors.	1
LIGHTS - COMPARTMENT, STEP & GROUND		
5380-0182	Ground light package EON LED - large.	1
5380-0247	Compartment light ROM V4 LED for medical cabinet (EA).	2
5380-0251	Compartment light package ROM V4 LED for medium bodies. Includes one light per compartment (two if transverse).	1
5380-0285	Step light package body TecNiq T440 4" LED - small.	1
5380-0323	The auxiliary steps below the cab doors to have EON LED lights to illuminate the	1

Salescode	Extended Description	Qty
LIGHTS - COMPARTMENT, STEP & GROUND		
	stepping surface and ground below (1PO lights indicated in the main ground light package).	
5380-0325	EON LED ladder tunnel light (EA).	2
LIGHTS - DECK AND SCENE		
5390-0025	Cab scene lights are to be switched with cab doors in addition to standard.	1
5390-0230	Hose bed light FireTech model WL2000 LED. Locate center front of hose bed. Switched with work light switch in cab.	1
5390-0241	FireTech 35" 12V mini brow light with back-up camera and white housing. Includes switch in cab accessible to driver. Monitor not included. Location: rear of body.	1
5390-0338-397	Whelen C6 Super LED scene lights (PR) with weatherproof connectors. Switch in cab (driver and officer side lights switched separately). Locate (1) each side of cab, rearward of forward doors, up high.	1
LIGHTS - NON-WARNING		
5400-0008	(1) pump panel light over the pump control area to be wired to come on when pump shift is placed in pump. (Side mount forward light noted, Top Mount is center light.)	1
5400-0137	Pump panel LED light package for side mount eMAX. Includes (6) Techniq EON lights with S/S housings, located (3) each side above lower side intake/discharge panels. Includes S/S light shields. SM eMAX only.	1
5400-0219-202	EON LED pump panel light - additional (EA). Location: driver side pump panel.	1
5400-0219-203	EON LED pump panel light - additional (EA). Location: officer side pump panel.	1
5400-0222	Pump compartment light Optronics ILL22 Series LED (EA). Includes separate on/off switch inside pump access door / panel. Light circuit to be wired through battery switch.	1
5400-0224	Engine compartment light Optronics LED Series ILL22 (EA).	1
CONTROLS / SWITCHES		
1750-0034-07G	Switch, additional 12 volt/15 amp. Location and function: programmed to multiplex display for aerial 12V flood lights at tip.	1
1750-0034-1CW	Switch, additional 12 volt/15 amp. Location and function: through multiplex display for rear facing scene lights.	1
5100-0006-199	Foot switch to control Q2B located officer's side.	1
5100-0011-T19	Switch 12V for 120-240V (EA). Location: programmed to multiplex display for 120/240V scene light(s) at tip of aerial (aerial circuit).	1
5100-0165	Audible door ajar alarm wired through door ajar light. For use with multiplex	1

Salescode	Extended Description	Qty
CONTROLS / SWITCHES		
display(s) only.		
CAMERAS / INTERCOM		
5350-0060	Diamond plate camera shield.	1
5350-0182	Safety Vision officer's side camera SV-622RS w/ SV-512 cable. Requires Safety Vision back-up camera option. Camera to be located on front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with right turn signal. Camera only - does not include monitor.	1
5350-0183	Safety Vision driver's side camera SV-622LS w/ SV-512 cable. Requires Safety Vision back-up camera option. Camera to be located on front cab corner (approx 31" bottom of camera to bottom of cab) interlocked with left turn signal. Camera only - does not include monitor.	1
5350-0192	Safety Vision back-up camera wired through multiplex display. Video displays automatically when transmission is in reverse. Camera only - does not include monitor.	1
5350-0244-202	FRC ACT 3-way aerial intercom to provide communications between the turntable control station, the aerial tip and driver side pump panel.	1
MISC ELECTRICAL		
5110-0004	Alternating flasher for headlights. Not available on Ford chassis.	1
5110-0017	Back-up alarm 97 dB.	1
5110-0018-755	12 volt 12 gauge constant hot lead (24" long) with ground wire. Location: R1 upper forward wall.	1
5110-0219-762	Blue Sea 12V power distribution module model 5032. Location: behind officer's seat.	1
GENERATOR		
5250-0040-121	Generator Harrison 6KW MCR hydraulic. Includes generator control / PTO engage switch and a gauge panel located adjacent to breaker box. Generator location: dunnage pan offset to driver side.	1
GENERATOR TEST		
5255-0001	3rd party generator test with pump.	1
BREAKER BOXES		
5200-0001-477	Breaker box 12 place single phase. Includes main breaker. Note: If gen is 6KW or less, main will occupy 2 places leaving 10 available. Locate L1 back wall above offset forward area.	1
LIGHTS - QUARTZ		

Salescode	Extended Description	Qty
LIGHTS - QUARTZ		
5450-0293	FireTech 72" 12V brow light with integrated marker lights and white housing. Includes switch accessible to driver. Replaces front brow marker lights. Requires special bracket 5450-0340 on aerials with waterway trough. Not available on aerials with deep trough.	1
RECEPTACLES		
5470-0001-060	Receptacle twist lock 20A/110V 3 wire NEMA L5-20 with cover plate. Location: officer side front compartment face.	1
5470-0001-062	Receptacle twist lock 20A/110V 3 wire NEMA L5-20 with cover plate. Location: driver side front compartment face.	1
5470-0001-503	Receptacle twist lock 20A/110V 3 wire NEMA L5-20 with cover plate. Location: over driver forward comprt for portable light.	1
5470-0004-1AT	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: R2 back wall up high centered.	1
5470-0004-763	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: rear wall of driver side medical compartment up high.	1
5470-0004-764	Receptacle household 20A/110V duplex 3-prong NEMA 5-20 with cover plate interior mounted wired to inlet receptacle. Location: rear wall of officer side medical compartment up high.	1
ELECTRIC CORD REELS		
5130-0002-413	Cord reel electric with 200' of 10/3 yellow cable. Location(s): ceiling mount turntable access door area.	1
5130-0012-413	Junction box Circle-D with four (4) 3-wire NEMA L5-15 110 volt 15 amp twist lock receptacles. Located on cord for reel in ceiling mount turntable access door area.	1
5130-0014-413	Circle D wall/floor mounting box. Mount at final or ship loose (customer preference). For use with reel located in or on ceiling mount turntable access door area.	1
5130-0022-786	Rollers for cord reel mounted through panel. Location(s): on turntable access door on right side of D-ring.	1
5130-0024-511	Electric cord reel rewind switch. Switch located rear of body near cord reel compartment.	1
5130-0028	Rollers, captive for cord reel mounted on reel. {May include a bracket (as required)}	1
AERIAL MODEL		
6100-0005	Ladder HP75 with waterway. Includes left side console with cover, split steps at	1

Salescode	Extended Description	Qty
AERIAL MODEL		
	tip and jack leg flood lights.	
AERIAL HYDRAULIC SYSTEM OPTIONS		
6150-0001	Aerial hydraulic filter isolation kit.	1
6150-0003-216	Gauge aerial hydraulic oil level. Electronic display to be located on pump operator's panel.	1
AERIAL CONTROLS		
6850-0011	Gas spring for aerial ladder console cover. To hold cover open at 90 degrees to the side.	1
6850-0026	Direct hydraulic aerial control system.	1
6850-0046	Retraction stops for ladder to keep monitor or other aerial components ahead of cab. May affect OAL.	1
MONITORS		
6300-0017	Monitor painted silver from OEM.	1
6300-0041	Monitor controls on pump operators panel. Ladders only. Note: Grayhill switchpad will be provided on units with AACS.	1
6300-0124	Monitor Akron StreamMaster II w/1578 SabreMaster II electric nozzle 1000 GPM for ladder. Includes tip and base controls.	1
AERIAL WARNING LIGHTS		
6550-0011	Outrigger warning lights (PR). Weldon Model 1010.	1
6550-0102-000-4T	Warning light Whelen ION-T Series model TLI Super LED at ladder tip (PR). Color: Red with clear lenses. Switched with aerial master. (Split light head(s) containing "white" light(s) are for additional or non-NFPA warning lights only - NOT for use in a NFPA compliant package.) Note: ION-T Series light only available with clear lenses.	1
AERIAL LIGHTING		
6560-0078-000-H2	Ladder climbing lights Luma Bar Pathfinder LED strip for HP75/78 ladder (one side). Color: Red (base) / White (2nd) / Blue (fly).	1
6560-0102-231	Light Whelen Pioneer Plus model PFP2AC with permanent mount. Requires 110V receptacle at tip option. Location(s): left side tip.	1
6560-0102-232	Light Whelen Pioneer Plus model PFP2AC with permanent mount. Requires 110V receptacle at tip option. Location(s): right side tip.	1
6560-0102-233	Light Whelen Pioneer Plus model PFP2AC with permanent mount. Requires 110V receptacle at tip option. Location(s): left side tip of base section.	1
6560-0102-234	Light Whelen Pioneer Plus model PFP2AC with permanent mount. Requires 110V	1

Salescode	Extended Description	Qty
AERIAL LIGHTING		
6560-0127	receptacle at tip option. Location(s): right side tip of base section. FireTech model FT-WL3500-FT-W LED flood/spot light with white housing. Includes hardwired switch on turntable console. Location: left and right side of base section.	1
6560-0202-231	FireTech model FT-WL-X-9-FT-W-SH LED flood/spot light with white housing. Includes switch on lighthouse and turntable console. Location: left side tip.	1
6560-0202-232	FireTech model FT-WL-X-9-FT-W-SH LED flood/spot light with white housing. Includes switch on lighthouse and turntable console. Location: right side tip.	1
WATERWAY OPTIONS		
6350-0000	Pinned waterway - upgrade. Waterway pins to section 2 or 3 on HP75 / HP78 and to section 3 or 4 on LTH100, HM100, HR100 and CR100.	1
6350-0001	Nozzle Guard.	1
6350-0005	Rear 4" NST waterway inlet for rear mounted aerials. Includes chrome cap.	1
6350-0008	Waterway shut-off valve. Mounted to allow waterway to be used as a discharge. (Available on 1000 GPM waterway only - N/A with Waterous pumps on 4-jack aerials.)	1
6350-0010	Flowminder with single readout and totalizer for the aerial waterway to be located at the aerial control station.	1
6350-0070	4" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. Locate next to waterway inlet.	1
MISC AERIAL ELECTRICAL		
6570-0015	110V/20A twist lock receptacle at tip.	1
6570-0038	Cradle alignment light on turntable console.	1
AERIAL EQUIPMENT		
6500-0023	Dual rope roller for aerial.	1
6500-0024	Lifting eye at tip of ladder. N/A on LTH/HM100 with pinned wway to tip.	1
6500-0025	Rear hand rail extension (PR) on turntable for center access step on rear of the body. HP75 / HP78 center hose bed only.	1
6500-0149-1CH-5V	Stokes basket storage brackets for use with Ferno Model 71 Stokes. The stokes basket shall mount to the base section on the right side toward rear. Stokes not included.	1
AERIAL LADDER BRACKETS		
6600-0002-248	Roof ladder bracket J style mount. Locate outside base section for a PRL-14 on left side of base section. Available on HP75/78, HP100, and HP95.	1

Salescode	Extended Description	Qty
SIGN PLATES		
6750-0000-000-39	Aerial sign plates 10 x 144 (PR). Available on Booms, HP75 and HP100 only. Does not include lettering. Color: Job Color.	1
AERIAL TESTING		
6900-0000	Aerial flow test - 3rd party.	1
6900-0007	Aerial 2016 NFPA Certification.	1
GROUND LADDERS		
7800-0007	Alco-Lite PRL-14' roof ladder.	1
7800-0010	Alco-Lite PRL-16' roof ladder.	2
7800-0016	Alco-Lite PEL-24' 2-section extension ladder.	2
7800-0023	Alco-Lite PEL3-35' 3-section extension ladder.	1
7800-0032	Alco-Lite FL-10, 10' folding ladder w/safety shoes.	1
MISC LOOSE EQUIPMENT		
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1
EXTERIOR PAINT		
8100-0084	All applicable pump/pre-connect application modules are to have a job color finish. Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1
8100-0085	Paint end of fly section job color. Includes nozzle guard (if equipped).	1
8100-0087	Paint Sample Spray Out - Dealer is responsible for returning written approval prior to order release. Two-tone cab color.	1
8100-0100	Special paint break. See sketch / drawing / photo in sales file.	1
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1
8100-0176-000-24	Paint E-ONE chassis cab - Sikkens paint. Color: FLNA3035 Red.	1
8100-0177-000-30	Paint cab Sikkens two-tone. Upper area of cab to be painted FLNA4095 White.	1
8100-0183-000-24	Paint Body - Large - For Aerials, T/A Tankers/Wetsides, Rear Mounts and Rescues. Sikkens paint. Color: FLNA3035 Red.	1
8100-0354	Paint lift cylinders, extension cylinders and upper turntable steelwork primary job color (does not apply to TT deck).	1
8100-0416	Front cab grille mesh painted with the waving United States flag.	1

Salescode	Extended Description	Qty
INTERIOR PAINT		
8150-0011	The interior of the cab to be painted Zolatone gray.	1
LETTERING		
8200-0113	Scotchlite Letter (Each) upto 6" tall. The exact size, color and location of the letters as specified by the customer.	150
8200-0114	Scotchlite Letter (Each) upto 12" tall. The exact size, color and location of the letters as specified by the customer.	15
8200-0116	Shade and/or outline (EA) for letters as specified by the customer.	160
STRIPING		
8300-0042	White rubrail scotchlite insert.	1
8300-0145-000-J7	Chevron "A" style 6" 3M "Diamond Grade" striping on front bumper. Colors to be Red/Fluorescent Yellow Green.	1
8300-0146-000-J7	Chevron "A" style 6" 3M "Diamond Grade" striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Red/Fluorescent Yellow Green.	1
8300-0227-000-J7	Diamond Grade reflective tape on (2) outriggers. Striping to alternate in an "A" pattern when viewed from the front or rear of the truck. Colors to be: Red/Fluorescent Yellow Green.	1
8300-0331	Single NFPA Scotchlite Stripe - up to 6" wide with hockey style, Z or S style or other customer specific design style. Stripe to be installed on cab and the body. Size, color and location as specified by the customer.	1
8300-0334	Additional NFPA Scotchlite Stripe - upto 3" wide on cab and the body. Design, size, color and location as specified by the customer.	2
8300-0335	A 1/4 in tape pin stripe above and below the scotchlite stripe(s). Color as specified by the customer.	1
8300-0338	Paint break Scotchlite cab stripe - 3/4" wide with customer specified color. To be located above existing paint break.	1
8300-0381	Yellow perimeter marking to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901 consisting of individual Reflexite diamonds approximately 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from this requirement.	1
GRAPHICS		
8400-0024-1V4	Install up to 12" SignGold customer logo from an existing E-ONE design (EA). Location: reference graphics layout drawing.	3
8400-0033	Logo E-ONE (PR) on aerial lift cylinder. Logo to be sign gold material approx 14" long located midway along outward surface of cylinder.	1

Salescode	Extended Description	Qty
WARRANTY / STANDARD & EXTENDED		
9100-0000	Standard 1 Year Warranty.	1
9100-0003	Lifetime Frame Structural Warranty.	1
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1
9100-0007	20 Year Aerial Device Structural Warranty - Integrity Limited Warranty.	1
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1
9100-0090	25 Year frame rail corrosion warranty. Includes liners (if equipped).	1
9100-0101	Meritor 5 year unlimited miles, parts and labor front axle warranty for non-drive axle or a 2 year unlimited miles, parts and labor warranty for front drive axle.	1
9100-0102	Meritor 5 year unlimited miles, parts and labor rear drive single or rear drive tandem axle warranty.	1
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS		
9300-0000	Vehicle familiarization aerial (Domestic). 3 days. Use 9300-0315 for additional days.	1
9300-0009	Manuals, Operator and Service in digital format.	1
9300-0012	Pump panel approval drawings. Will be provided on purchased units prior to construction.	1
9300-0016	Approval Drawings-Standard.	1
9300-0031	Dash/Console panel layout approval drawings. Will be provided on purchased units prior to construction.	1
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1
Dealer Supplied Equipment		